

CUSTOMER NO.: 24498**Serial No.: 10/043,540**

RCE Reply to Final Office Action dated: 07/12/07

Preliminary Amendment Dated: 10/09/07

PATENT**PU020013**RECEIVED
CENTRAL FAX CENTER

OCT 10 2007

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims

1. (Currently amended) An asynchronous transfer mode (ATM) digital document delivery system, comprising:
 - a customer premise unit configured to permit a customer to order and receive a data stream;
 - a buffer coupled to the customer premise unit to store the data stream before transmitting the data stream to a customer;
 - a server having digital documents stored thereon for delivery to the customer through a switched ATM network; and
 - means for controlling a data rate of the data stream between the server and the buffer to ensure maintenance of a steady data stream from the customer premise unit to the customer during a loss of a physical layer between the server and the customer premise unit, the means for controlling including a network control system coupled to the server and the customer premise unit, the network control system configured for increasing providing control for the data rate of the data stream to the customer premise unit from the server for a period of time when the physical layer is restored, and a multiplexer coupled between the customer premise unit and the network control system, the multiplexer including a signaling mechanism to alert at least one component that the physical layer is lost.
2. (Original) The document delivery system, as recited in claim 1, wherein the customer premise unit includes the buffer therein, the buffer including a memory storage capacity sufficient to maintain the data stream to a customer for an amount of time.
3. (Original) The document delivery system, as recited in claim 2, wherein the amount of time includes time needed to restore the physical layer.

CUSTOMER NO.: 24498**Serial No.: 10/043,540**

RCE Reply to Final Office Action dated: 07/12/07

Preliminary Amendment Dated: 10/09/07

PATENT**PU020013**

4. (Original) The document delivery system, as recited in claim 2, wherein the amount of time includes up to 30 seconds.

5. (Cancelled)

6. (Cancelled)

7. (Previously presented) The document delivery system, as recited in claim 1, further comprising virtual circuits set up between the network control system, the customer premise unit and the multiplexer to enable communication therebetween.

8. (Original) The document delivery system, as recited in claim 1, wherein the server is configured to deliver the data stream at a rate greater than a normal rate after the physical layer has been restored.

9. (Original) The document delivery system, as recited in claim 8, wherein the server is configured to deliver the data stream at the normal rate after the buffer has been filled.

10. (Original) The document delivery system, as recited in claim 1, wherein the customer premise unit is configured to deliver the data stream at a rate less than a normal rate when the physical layer is lost.

11. (Currently amended) A method for maintaining a data stream over an asynchronous transfer mode (ATM) network, comprising the steps of:
providing a customer premise unit configured to permit a customer to receive a data stream;
storing a portion of the data stream in a buffer before transmitting the data stream to a customer;
transmitting the data stream from a server through a switched ATM network;
and
controlling a data rate of the data stream between the server and the buffer to ensure maintenance of a steady data stream from the customer premise unit to a customer during a loss of a physical layer between the server and the

CUSTOMER NO.: 24498**Serial No.: 10/043,540**

RCE Reply to Final Office Action dated: 07/12/07

Preliminary Amendment Dated: 10/09/07

PATENT**PU020013**

customer premise unit, the controlling includes employing a network control system coupled to the server and the customer premise unit and further comprising the step of the network control system increasing providing control for the data rate of the data stream to the customer premise unit from the server for a period of time when the physical layer is restored, and a multiplexer coupled between the customer premise unit and the network control system, and further comprising the step of: when the physical layer is lost, signaling from the multiplexer to alert at least one component that the physical layer is lost.

12. (Original) The method as recited in claim 11, wherein the step of controlling a data rate of the data stream includes maintaining an amount of data from the data stream in the buffer to continue data flow to a customer for an amount of time after the loss of the physical layer.

13. (Original) The method as recited in claim 12, wherein the amount of time includes time needed to restore the physical layer.

14. (Cancelled)

15. (Cancelled)

16. (Previously presented) The method as recited in claim 11, further comprising the step of setting up virtual circuits between the network control system, the customer premise unit and the multiplexer to enable communication therebetween.

17. (Original) The method as recited in claim 11, further comprising the step of delivering the data stream from the server at a rate greater than a normal rate after the physical layer has been restored.

18. (Original) The method as recited in claim 17, further comprising the step of delivering the data stream at the normal rate after the buffer has been filled.

CUSTOMER NO.: 24498

Serial No.: 10/043,540

RCE Reply to Final Office Action dated: 07/12/07

Preliminary Amendment Dated: 10/09/07

PATENT

PU020013

19. (Original) The method as recited in claim 11, further comprising the step of delivering the data stream from the customer premise unit to a customer at a rate less than a normal rate when the physical layer is lost.